

360°

Schoeller Allibert Returnable Plastic Packaging Solutions

 TankGo® 3000



Schoeller Allibert
Innovating your logistics for a better world

TankGo® 3000: UN Certified for transporting hazardous liquid products

Peace of mind and safety for transporting chemical products

Profitability

Reusable throughout their service life, in line with UN Certification for the transport of hazardous materials.

Anti-corrosive protection

TankGo 3000 is 100% plastic, ensuring it is maintenance free. All of the main parts are made from plastic which means no oxidation and no maintenance.

Intensive reuse

Thick-walled rotationally molded tank and structure to effortlessly withstand impacts and frequent handling.

Safe transport

Centering points for straps to safe the load in the truck.

Scale volume

Scale volume engraved directly on to the front of the tank.
Volume level every 250 l.

Extra venting

More accessible venting system. Reinforced and transparent pipe.

Safe handling

4 rigid pivots for safe, stable unladen stacking.
3 Eye bolts in the upper part of the container for anchoring safety belts and/or safety harnesses.

Personalisation

Available in a choice of colours, on request.

Brand awareness and identification

Optional personalisation through the marking of logos, registration and instructions.
2 areas for adhesive labels (3 rhombus 10x10cm size) on both short sides.
2 areas for adhesive labels (300x210mm) on both short sides.
1 area for engraved customer brand, short side only.

UN, ADR, RID, IMDG certified

Certified for the transport and storage of hazardous materials. Manufactured according to rigorous EU regulations.
Homologation plate number fixed on the front part of the IBC.

Easy handling

Forklift entries, in each long side.
One on the back short side.

Practical, safe to use

Easy access to the reinforced valve guarantees full drainage or emptying.

Versatile, large capacity

Unique worldwide: 100% plastic
3000 Litres IBC.
No oxidation and no maintenance.



TankGo® 3000



> Reference	8357000
Use	Transport and storage of corrosive liquids
Version	UN, ADR, RID, IMDG certified
Homologation Num	UN 31HH1/Y/*E/SCHOELLER ALLIBERT / G-10000/0/5345/340kg/3000L/110KPa
Standard liquids	Water, Acetic Acid 98-100%, Nitric Acid 55% and 65 %, Butyl Acetate 98-100%, Tensioactives Solution, White Spirit
Usable volume	2940 litres
Overflow capacity	3000 litres
Maximum density	1.7 gr/cm ³
Service life	The bottle must be changed every 5 years
Manufactured	Virgin polyethylene
Length x width	2385 x 1570 mm.
Height	1870 mm.
Weight	340 kg.
Stacked during transport	0
Stacked unladen	1/1
Maximum gross weight	5345 kg.
Top screw cap	Threaded DN150 EPDM or Viton sealing gasket
Outlet	Ball valves in PPFV, PE-PVDF, DN50
Ventings	2 positions in accordance with legislation Automatic anti-depression venting Frontal venting valve
Optional	Customisation logos by mass engraving
Tank colour	Natural
Colour cover/pallet part	Black / Red / Green / Blue

Ergonomic


Two ladders available, short and long side. Steps with anti-slip surface.



Easy handling

Forklift entries in each long side. One on the back short side.

Ergonomic handles



Anti-depression venting

Preventing collapsing of the tank in case of sudden discharge.

> Accessories



> Frontal venting, valve DN25



> Ball valve DN50 in GRP, Viton sealing gasket



> Cover DN150 special Viton sealing gasket



> Two-position venting, Viton sealing gasket



> Anti-depression venting



> Ball valve DN50 in GRP, EPDM sealing gasket



> Threaded cover DN150 EPDM sealing gasket



> Two-position venting, EPDM sealing gasket

> Enquire for other types of valves



Schoeller Allibert

Innovating your logistics for a better world



Visit our website
www.schoellerallibert.com